


Guangzhou Jiguang Lighting Co.,Ltd

T8 LED Tube Light



Dimension



| Length | A (mm) | B (mm) | C (mm) | D (mm) |
|--------|--------|--------|--------|--------|
| 2FT | 588 | 603 | 26 | 32 |
| 4FT | 1198 | 1213 | 26 | 32 |
| 5FT | 1498 | 1514 | 26 | 32 |
| 8FT | 2372 | 2387 | 26 | 32 |

Features

- ★ Instant on, no flicker or buzz .
- ★ High power factor over 0.95 .
- ★ Aluminum + PC materials , good heat dissipating .
- ★ Replace t8 fluorescent tube directly , fit well into existing t8 fixture .

Benefits

- ★ Mercury-free , no hazardous waste disposal .
- ★ Suitable for operation at low temperatures .
- ★ Energy saving of up to 65% compared to T8 fluorescent lamp .

Application

- ★ Corridors, stairways , parking garages .
- ★ Industry, warehouses
- ★ Building , office , home , school .
- ★ Supermarkets and department stores , shops, etc.
- ★ Outdoor application only with suitable luminaries or housing .

Specification

| Model No. | Length | Power | LED Chip | Input Voltage | Power Factor | Lumens Output | Color Temperature | CRI | Life Time | Beam Angle |
|-------------|--------------|-------|----------|---------------|--------------|---------------|-------------------|-------|------------|------------|
| CP-T806-9W | 600mm / 2ft | 9W | SMD2835 | 100-240V AC | 0.93 | 990 lm | 2700K-7000K | Ra>80 | 50,000 Hrs | 160° |
| CP-T812-16W | 1200mm / 4ft | 16W | SMD2835 | 100-240V AC | 0.97 | 1760 lm | 2700K-7000K | Ra>80 | 50,000 Hrs | 160° |
| CP-T812-18W | 1200mm / 4ft | 18W | SMD2835 | 100-240V AC | 0.97 | 1980 lm | 2700K-7000K | Ra>80 | 50,000 Hrs | 160° |
| CP-T812-20W | 1200mm / 4ft | 20W | SMD2835 | 100-240V AC | 0.97 | 2100 lm | 2700K-7000K | Ra>80 | 50,000 Hrs | 160° |
| CP-T812-22W | 1200mm / 4ft | 22W | SMD2835 | 100-240V AC | 0.97 | 2300 lm | 2700K-7000K | Ra>80 | 50,000 Hrs | 160° |
| CP-T815-23W | 1500mm / 5ft | 23W | SMD2835 | 100-240V AC | 0.97 | 2450 lm | 2700K-7000K | Ra>80 | 50,000 Hrs | 160° |
| CP-T815-25W | 1500mm / 5ft | 25W | SMD2835 | 100-240V AC | 0.97 | 2650 lm | 2700K-7000K | Ra>80 | 50,000 Hrs | 160° |
| CP-T824-36W | 2400mm / 8ft | 36W | SMD2835 | 100-240V AC | 0.97 | 3950 lm | 2700K-7000K | Ra>80 | 50,000 Hrs | 160° |

OEM Service

- ★ Can customize different length
- ★ Can customize higher CRI
- ★ Can customize higher brightness

Packing

| Length | Carton Size | PCS/CTN | Volume | Gross Weight |
|--------|--------------|---------|------------|--------------|
| 2FT | 127*22*22 cm | 50 | 0.0615 CBM | 7.0 kg |
| 4FT | 127*22*22 cm | 25 | 0.0615 CBM | 6.5 kg |
| 5FT | 157*22*22 cm | 25 | 0.0759 CBM | 7.5 kg |
| 8FT | 245*22*15 cm | 15 | 0.0809 CBM | 9.0 kg |