

Guangzhou Jiguang Lighting Co.,Ltd

PIR Sensor T8 LED Tube Light



Features

- ★ Instant on, no flicker or buzz .
- ★ High power factor over 0.95 .
- ★ Aluminum + PC materials , good heat dissipating .
- ★ Work with sensor , intelligent and energy saving .


Microwave Sensor T8 LED Tube Light



Benefits

- ★ Mercury-free , no hazardous waste disposal .
- ★ Suitable for operation at low temperatures .
- ★ Sensor control , intelligent and energy saving .

Dimension



Length	A (mm)	B (mm)	C (mm)	D (mm)
2FT	588	603	26	32
4FT	1198	1213	26	32
5FT	1498	1514	26	32

Application

- ★ Corridors, stairways , parking garages .
- ★ Industry, warehouses
- ★ Building , office , home , school .
- ★ Supermarkets and department stores , shops, etc.
- ★ Outdoor application only with suitable luminaries or housing .

Specification

Model No.	Length	Power	LED Chip	Standby Power	Detective Distance	Time Delay	Lumens Output	Color Temperature	Input Voltage	Life Time	Beam Angle
PIR Sensor T8 LED Tube											
CP-T806-9WPIR	600mm / 2ft	9W	SMD2835	3W / 0W	5-6m	25s-60s	990 lm	2700K-7000K	100-240V AC	50,000 Hrs	160°
CP-T812-18WPIR	1200mm / 4ft	18W	SMD2835	3W / 0W	5-6m	25s-60s	1980 lm	2700K-7000K	100-240V AC	50,000 Hrs	160°
CP-T815-23WPIR	1500mm / 5ft	23W	SMD2835	3W / 0W	5-6m	25s-60s	2450 lm	2700K-7000K	100-240V AC	50,000 Hrs	160°
Microwave Sensor T8 LED Tube											
CP-T506-9WRD	600mm / 2ft	9W	SMD2835	3W / 0W	5-12m	25s-60s	990 lm	2700K-7000K	100-240V AC	50,000 Hrs	160°
CP-T512-18WRD	1200mm / 4ft	18W	SMD2835	3W / 0W	5-12m	25s-60s	1980 lm	2700K-7000K	100-240V AC	50,000 Hrs	160°
CP-T515-23WRD	1500mm / 5ft	23W	SMD2835	3W / 0W	5-12m	25s-60s	2450 lm	2700K-7000K	100-240V AC	50,000 Hrs	160°

Packing

Model No.	CP-T806-9WPIR	CP-T812-18WPIR	CP-T815-23WPIR	CP-T506-9WRD	CP-T512-18WRD	CP-T515-23WRD
Carton Size	127*22*25cm	127*22*25cm	157*22*25cm	127*22*22cm	127*22*22cm	157*22*22cm
PCS/CTN	50	25	25	50	25	25
Volume	0.0699 CBM	0.0699 CBM	0.0864 CBM	0.0615 CBM	0.0615 CBM	0.0759 CBM
Gross Weight	7.5kg	7kg	8kg	7.5kg	7kg	8kg

Add.:4th Floor, Building 2, #38, Longgang Road, Baiyun District, Guangzhou 510445, China
Tel: +86-(020) 23323729 Fax:+86-(020) 23323729